



SP 5000 TR

Product information

Triple-beam laser interferometer for simultaneous and precise length, pitch and yaw angle measurements

Laser interferometer measurement system

SP 5000 TR


Many applications in industry and research require high-precision simultaneous displacement and angle measurements. Fast set-up and uncomplicated adjustment are particularly important.

Triple-beam laser interferometers are precision length measuring devices that combine three interferometers in one device. The same highly stable laser frequency is used in all three measuring channels. Thus, three length values can be measured simultaneously with nanometer accuracy. The corresponding angle can be determined with high precision from the difference between two length values and the calibrated beam distance. The system has a modular design and can therefore be adapted to a wide variety of measurement tasks.

The fiber optic coupling of the sensor head and the optionally integrated beam direction detection support easy handling and adjustment.

The design of the three-beam interferometer is compact and robust. This makes it ideal for high-precision measurements in industry and research and as an OEM instrument.

For large measuring ranges or calibration tasks, the use of wireless temperature sensors or the climate measuring station LCS is recommended.



**up to 5m
and more**



20 pm



0.1 µm/m




**± 12.5° with reflector
± 1.5' with plane-
mirror**



**0.002
arcsec**

MEASURING PRINCIPLE



Simultaneous measurements
of lengths and angles
with highest accuracy

Further possible applications:

- High-precision pitch and yaw angle correction for two- and multi-coordinate measurements
- Differential measurements (dilatometry, material testing, etc.)
- Dynamic angle measurements, acquisition of angle vibrations
- OEM and vacuum versions of the device are possible

Ideal for

- Quality assurance
- Calibration
- Development
- Science and research
- OEM applications

Triple-Beam Interferometer SP 5000 TR



System parameter	SP 5000 TR
Length measuring range	5 m
Length resolution	20 µm
Angular measuring ranges with reflector with plane mirror (recommended distance ≤2 m)	±12.5° ±1.5 arcmin
Angular resolution (at 0.1 nm length resolution)	0.002 arcsec
Beam distances (horizontal and vertical)	12 mm
Wavelength	632.8 nm
Frequency stability of the HeNe laser (after warm-up time)	2·10 ⁻⁸
Warm-up time of the HeNe laser	10...20 min
Operating temperature range	15...30°C
Max. displacement speed of measuring reflector	3 m/s

Geometric Data

Dimensions (L x W x H): Sensor head with adjustable mount Reflector Electronic supply and evaluation unit	[202 x 137 x 72] mm [45 x 45 x 20] mm [450 x 450 x 150] mm
Mass: Sensor head with adjustable mount Reflector Electronic supply and evaluation unit	1.9 kg 80 g ca. 9.5 kg

Electrical Data

Interfaces standard other interfaces on request	RS232C, USB
Cable length between sensor head and electronics unit	3 m, optionally up to 10 m
Power supply	100...240 VAC / 47...63 Hz
Laser safety class according to EN 60825-1:2014 and ANSI Z136.1 (CDRH)	2M II



<http://www.dct3d.com>

大慶科技儀器有限公司

701台南市東區長榮路一段256號6F-4

電話：(06)236-5697 傳真：(06)236-5698

email: jacky3d@dct3d.com